

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Union Carbide Corporation

AUTHORIZING THE OPERATION OF
Union Carbide Texas City
Utility Department
All Other Basic Organic Chemical Manufacturing

LOCATED AT
Galveston County, Texas
Latitude 29° 22' 30" Longitude 94° 56' 55"
Regulated Entity Number: RN100219351

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: Q1921 Issuance Date: December 21, 2015

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	10
New Source Review Authorization Requirements	11
Compliance Requirements.....	12
Risk Management Plan	13
Temporary Fuel Shortages (30 TAC § 112.15)	14
Permit Location	14
Permit Shield (30 TAC § 122.148)	14
Attachments	15
Applicable Requirements Summary.....	16
Additional Monitoring Requirements	84
Permit Shield	95
New Source Review Authorization References	100
Appendix A	105
Acronym List	106

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart H, Subpart EEE, Subpart ZZZZ and Subpart DDDDD, as identified in the attached Applicable Requirements Summary table

are subject to 30 TAC Chapter 113, Subchapter C, §113.130, §113.620, §113.1090 and §113.1130 which incorporate the 40 CFR Part 63 Subparts by reference.

- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.302 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
 - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
- (i) Title 30 TAC § 101.352 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
 - (vi) Title 30 TAC § 101.359 (relating to Reporting)
 - (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- H. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.372 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)
 - (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)

- (v) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit
- I. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
 - (i) Title 30 TAC § 101.392 (relating to Exemptions)
 - (ii) Title 30 TAC § 101.401 (relating to Level of Activity Certification)
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of

producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer’s eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is

not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources

operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- E. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- F. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)

- (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

- 4. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 5. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
 - H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
- 6. For facilities where total annual benzene quantity from waste is less than 1 megagram per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(5)(i) - (ii), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
 - B. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
 - C. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)

- D. Title 40 CFR § 61.357(a), and (b) (relating to Reporting Requirements)
- 7. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 8. For containers using controls specified in 40 CFR Part 63, Subpart PP, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.470 incorporated by reference):
 - A. Title 40 CFR § 63.922(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 1 Controls)
 - B. Title 40 CFR § 63.923(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 2 Controls)
 - C. Title 40 CFR § 63.925(a)(1) - (8), and (b)(1) - (3) (relating to Test Methods and Procedures)
 - D. Title 40 CFR § 63.926(a)(1) - (3) (relating to Inspection and Monitoring Requirements)
- 9. For site remediation projects subject to 40 CFR Part 63, Subpart GGGGG that will remove remediation material containing less than 1 megagram per year of the HAP listed in Table 1 to Subpart GGGGG, the permit holder shall comply with 40 CFR § 63.7881(c)(1) - (3) (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference).
- 10. For containers managing remediation materials subject to 40 CFR Part 63, Subpart GGGGG, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference):
 - A. Title 40 CFR § 63.922(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 1 Controls)
 - B. Title 40 CFR § 63.923(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 2 Controls)
 - C. Title 40 CFR § 63.925(a)(1) - (8), and (b)(1) - (3) (relating to Test Methods and Procedures)
 - D. Title 40 CFR § 63.926(a)(1) - (3) (relating to Inspection and Monitoring Requirements)
 - E. Title 40 CFR § 63.7901(b) and (b)(1), for initial demonstration of compliance
 - F. Title 40 CFR § 63.7901(b)(2), for initial demonstration of compliance
 - G. Title 40 CFR § 63.7901(c), (c)(1), and (c)(2), for initial demonstration of compliance
 - H. Title 40 CFR § 63.7901(d), and (d)(1) - (4), for initial demonstration of compliance
 - I. Title 40 CFR § 63.7903(b) and (b)(1), for continuous demonstration of compliance
 - J. Title 40 CFR § 63.7903(b)(2), (b)(2)(i), (b)(2)(ii), for continuous demonstration of compliance

- K. Title 40 CFR § 63.7903(c)(4), (c)(4)(i), and (c)(4)(ii), for continuous demonstration of compliance
 - L. Title 40 CFR § 63.7903(d)(5), (d)(5)(i), and (d)(5)(ii), for continuous demonstration of compliance
 - M. Title 40 CFR § 63.7952(c), for recordkeeping
11. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

12. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached "CAM Summary" upon issuance of the permit. In addition, the permit holder shall comply with the following:
- A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the "CAM Summary," deviations as defined by the deviation limit in the "CAM Summary." Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached "CAM Summary," in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
13. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required

intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

14. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
15. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
16. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
17. The permit holder shall comply with the terms and conditions of the air addendum of the Industrial Hazardous Waste permit listed in the New Source Review Authorization Reference Attachment. Requirements other than those of the air addendum are not applicable to this operating permit.
18. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
 - C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.
 - D. Boiler Standard Permit

Compliance Requirements

19. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
20. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For electric utilities in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9120
 - B. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
 - (ii) For electric generating facilities in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020(2)(B)
 - C. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
 - D. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
21. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)

- (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
- (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)

22. Use of Discrete Emission Credits to comply with the applicable requirements:

- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

23. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Temporary Fuel Shortages (30 TAC § 112.15)

24. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
- A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
 - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
 - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
 - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Permit Location

25. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

26. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary	17
---------------------------	-----------

Applicable Requirements Summary	23
--	-----------

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
3RDSTENG1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
3RDSTENG1	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
3RDSTENG1	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart III	No changing attributes.
3RDSTENG1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
3RDSTENG2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
3RDSTENG2	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
3RDSTENG2	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart III	No changing attributes.
3RDSTENG2	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
5PHENG1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
5PHENG1	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
5PHENG1	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart III	No changing attributes.
5PHENG1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
5PHENG2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
5PHENG2	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Subchapter B	
5PHENG2	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart IIII	No changing attributes.
5PHENG2	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
6PHENG1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
6PHENG1	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
6PHENG1	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart IIII	No changing attributes.
6PHENG1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
6PHENG2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
6PHENG2	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
6PHENG2	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart IIII	No changing attributes.
6PHENG2	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
AS-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
AS-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115VGC	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E02B030	EMISSION POINTS/STATIONARY	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
E02B030	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115VGC	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7ICI-1	30 TAC Chapter 117, Subchapter B	Fuel Type #1 = Natural gas.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7ICI-2	30 TAC Chapter 117, Subchapter B	Fuel Type #1 = Renewable non- fossil fuel gas other than landfill gas., Fuel Type #2 = Natural gas.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7ICI-3	30 TAC Chapter 117, Subchapter B	Fuel Type #1 = Renewable non- fossil fuel gas other than landfill gas., Fuel Type #2 = Natural gas., Fuel Type #3 = Liquid fuel.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7ICI-4	30 TAC Chapter 117, Subchapter B	Fuel Type #1 = Natural gas., Fuel Type #2 = Liquid fuel.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-2	40 CFR Part 60, Subpart Db	No changing attributes.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-3	40 CFR Part 60, Subpart Db	No changing attributes.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-4	40 CFR Part 60, Subpart Db	D-Series Fuel Type #1 = Hazardous waste., D-Series Fuel Type #2 = Natural gas., Heat Release Rate = Natural gas with a heat release rate

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					less than or equal to 70 MBtu/hr/ft ³ ., Heat Input Gas/Oil = The facility combusts natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63EEE-1	40 CFR Part 63, Subpart EEE	Heating Value = The hazardous waste as-fired heating value is less than 10,000 Btu/lb.
E02B030	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63EEE-2	40 CFR Part 63, Subpart EEE	Heating Value = The hazardous waste as-fired heating value is 10,000 Btu/lb or greater.
E02BCTR1	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR2	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR4	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR5	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR6	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR7	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E02BCTR9	INDUSTRIAL PROCESS COOLING TOWERS	N/A	115H2	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
E17A020	LOADING/UNLOADING	N/A	R5211	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	OPERATIONS			Loading and Unloading of VOC	
F02B0001	FUGITIVE EMISSION UNITS	N/A	61J	40 CFR Part 61, Subpart J	No changing attributes.
F02B001-01	FUGITIVE EMISSION UNITS	N/A	61J	40 CFR Part 61, Subpart J	No changing attributes.
F02B001-01	FUGITIVE EMISSION UNITS	N/A	63H	40 CFR Part 63, Subpart H	No changing attributes.
F17A001	FUGITIVE EMISSION UNITS	N/A	R5780-ALL	30 TAC Chapter 115, HRVOC Fugitive Emissions	No changing attributes.
F17A001	FUGITIVE EMISSION UNITS	N/A	61J	40 CFR Part 61, Subpart J	No changing attributes.
F17A001	FUGITIVE EMISSION UNITS	N/A	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.
GRP UDTK1	STORAGE TANKS/VESSELS	T17ARSRH2O, T17ASH2O	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
LLENG1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
LLENG1	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117, Subchapter B	No changing attributes.
LLENG1	SRIC ENGINES	N/A	60IIII-01	40 CFR Part 60, Subpart IIII	No changing attributes.
LLENG1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
LLENG2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
LLENG2	SRIC ENGINES	N/A	R7201	30 TAC Chapter 117,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Subchapter B	
LLENG2	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart IIII	No changing attributes.
LLENG2	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
T03AD2054T	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T03AD2427	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T03AD2550	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T03AIPDAN	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T03AIPDAS	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T03AY2048T	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5137	30 TAC Chapter 115, Water Separation	No changing attributes.
T03AY2050T	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5137	30 TAC Chapter 115, Water Separation	No changing attributes.
W03A005	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
W03A005A	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
3RDSTENG 1	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
3RDSTENG 1	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
3RDSTENG 1	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						NMHC+NOx emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.			
3RDSTENG 1	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
3RDSTENG 1	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
3RDSTENG 2	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						which construction was begun after January 31, 1972.			
3RDSTENG 2	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
3RDSTENG 2	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
3RDSTENG 2	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4	Owners and operators of emergency stationary fire	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.			
3RDSTENG 2	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
5PHENG1	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
5PHENG1	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division	None	§ 117.340(j) [G]§ 117.345(f)(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)		[G]§ 117.345(f)(6)	
5PHENG1	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
5PHENG1	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4218	displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.			
5PHENG1	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
5PHENG2	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
5PHENG2	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new,	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
5PHENG2	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart III	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
5PHENG2	EU	60III-01	PM	40 CFR Part 60, Subpart III	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hr, as listed in Table 4 to this subpart.			
5PHENG2	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
6PHENG1	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
6PHENG1	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
6PHENG1	EU	60IIII-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
6PHENG1	EU	60IIII-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
6PHENG1	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
6PHENG2	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
6PHENG2	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						engines as specified. §117.303(a)(11)(A)-(B)			
6PHENG2	EU	60IIII-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
6PHENG2	EU	60IIII-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
6PHENG2	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
AS-2	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
AS-2	EP	115VGC	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2) § 115.126(3)(B)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(B)	None
E02B030	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 15%	[G]§ 111.111(a)(1)(F) ** See Periodic	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						averaged over a six minute period for any source with a total flow rate of at least 100,000 acfm unless a CEMS is installed.	Monitoring Summary		
E02B030	EP	115VGC	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(C)	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
E02B030	EU	R7ICI-1	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(3)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.320(a) § 117.320(b) [G]§ 117.320(c) § 117.320(i) § 117.320(j) § 117.320(k) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.320(d) [G]§ 117.320(e) § 117.320(h) § 117.320(k) [G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) §	§ 117.320(f) § 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.320(g) § 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
E02B030	EU	R7ICI-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(3)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.320(a) § 117.320(b) [G]§ 117.320(c) § 117.320(i) § 117.320(j) § 117.320(k) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.320(d) [G]§ 117.320(e) § 117.320(h) § 117.320(k) [G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A)	§ 117.320(f) § 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.320(g) § 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
E02B030	EU	R7ICI-3	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(3)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.320(a) § 117.320(b) [G]§ 117.320(c) § 117.320(i) § 117.320(j) § 117.320(k) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.320(d) [G]§ 117.320(e) § 117.320(h) § 117.320(k) [G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a)	§ 117.320(f) § 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.320(g) § 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
E02B030	EU	R7ICI-4	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(3)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.320(a) § 117.320(b) [G]§ 117.320(c) § 117.320(i) § 117.320(j) § 117.320(k) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.320(d) [G]§ 117.320(e) § 117.320(h) § 117.320(k) [G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1)	§ 117.320(f) § 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.320(g) § 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8100(c)
E02B030	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-1	PM	40 CFR Part 60,	§ 60.40b(a)	This subpart applies to each	None	[G]§ 60.49b(d)	§ 60.49b(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			(Opacity)	Subpart Db		steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).		§ 60.49b(o)	§ 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-2	SO ₂	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-2	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-2	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-3	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combusted in the unit > 29 MW (100 MMBtu/hr).			
E02B030	EU	60Db-3	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(2) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities with a low heat release rate and combusting natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels, a limit determined by use of the specified formula.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
E02B030	EU	60Db-4	SO ₂	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-4	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
E02B030	EU	60Db-4	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E02B030	EU	60Db-4	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(2) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities with a low heat release rate and combusting natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels, a limit determined by use of the specified formula.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
E02B030	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
E02B030	EU	63EEE-1	Dioxins/Furans	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(1)(ii) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) §	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain CO emissions in excess of the limits provided by §63.1217(a)(5) for sources not equipped with a dry air pollution control system;	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) [G]§ 63.1207(b)(2) [G]§ 63.1207(b)(3) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) § 63.1209(k)(2)(i) [G]§ 63.1209(k)(3)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) [G]§ 63.1207(l)(2) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(k) § 63.1209(k)(1)(i) § 63.1209(k)(2)(i) § 63.1209(k)(2)(ii) [G]§ 63.1209(k)(3) [G]§ 63.1209(k)(4) § 63.1209(k)(5) [G]§ 63.1209(k)(6) [G]§ 63.1209(k)(7) [G]§ 63.1209(k)(8) [G]§ 63.1209(k)(9) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)		63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(i)(A) § 63.1207(g)(1)(ii) § 63.1207(g)(2)(ii) § 63.1207(g)(2)(v) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) [G]§ 63.1208(b)(1) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(k)(2)(i) [G]§ 63.1209(k)(3) [G]§ 63.1209(k)(8) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)	[G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xix) § 63.1207(f)(1)(xv) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xxviii) [G]§ 63.1207(f)(1)(xx) [G]§ 63.1207(f)(1)(xxi) § 63.1207(f)(1)(xxii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(2) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-1	Mercury	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(2)(i) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1207(m)(3) [G]§ 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) [G]§ 63.1209(l)(1)(v) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain Hg, except as provided for in paragraph §63.1217 (a)(2)(iii), when you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 19 µg/dscm , corrected to 7 % O ₂ , on an (not-to-exceed) annual averaging period.	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(iii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) [G]§ 63.1207(f)(1)(x) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1208(b)(2) § 63.1208(b)(7)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) [G]§ 63.1207(f)(1)(ii) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) [G]§ 63.1207(f)(1)(x) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xvi) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxvi) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.1208(b)(8) § 63.1209(a)(5) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)		§ 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1207(m)(5) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) § 63.1209(g)(1)(iv)(B) [G]§ 63.1209(l)(1)(v) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-1	Total Chlorine	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(6)(i) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi)	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain hydrogen chloride and chlorine, except for an area source as defined under §63.2, when you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 31 ppmv, combined emissions, expressed as a chloride	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1209(b)(1)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1207(m)(3) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(n)(4) § 63.1209(o) § 63.1209(o)(1)(ii)(B) [G]§ 63.1209(o)(2) [G]§ 63.1209(o)(3) § 63.1209(o)(4) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)	(Cl-) equivalent, dry basis and corrected to 7 % 02.	63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xi) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) § 63.1207(g)(2)(iii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) [G]§ 63.1208(b)(5)(i) § 63.1208(b)(5)(ii) [G]§ 63.1208(b)(5)(ii)(B) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(a)(5) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) § 63.1209(c)(5) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q)	[G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xi) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xvi) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxv) § 63.1207(f)(1)(xxvi) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(iii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1207(m)(5) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.1209(r)		[G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-1	Principal Organic Hazardous Constituent	40 CFR Part 63, Subpart EEE	§ 63.1217(c)(1) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) [G]§ 63.1209(j) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(c)(3)(i) § 63.1217(c)(3)(ii)	For liquid fuel boilers, except as provided in §63.1217(c)(2), you must achieve a DRE of 99.99% for each POHC designated under paragraph §63.1217(c)(3). You must calculate DRE for each POHC using the equation in §63.1217(c)(2).	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(iii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) § 63.1207(f)(1)(ii)(D) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(b)(1)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(b)(7)(i) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) [G]§ 63.1206(c)(7) [G]§ 63.1206(c)(vii) [G]§ 63.1206(c)(xii) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) § 63.1207(f)(1)(ii)(D) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xix) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) [G]§ 63.1209(j) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)		§ 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-1	Total Hydrocarbons/CO	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(5)(i) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) §	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain CO in excess of 100 ppmv, over an hourly rolling average (monitored continuously with a CEMs), dry basis and corrected to 7 % O ₂ . If complying with this CO standard rather than the hydrocarbon standard under §63.1217(a)(5)(ii), hydrocarbons do not exceed 10 ppmv , and must be reported as specified.	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(b)(6) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) [G]§ 63.1207(f)(1)(ii) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)		§ 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) § 63.1207(g)(2)(i) § 63.1207(g)(2)(v) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(a)(1)(i) § 63.1209(a)(2) [G]§ 63.1209(a)(3) [G]§ 63.1209(a)(6) § 63.1209(a)(7) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)	[G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxviii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(i) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-2	Dioxins/Furans	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(1)(ii) [G]§ 63.1206(b)(5)	For existing liquid fuel boilers, you must not	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) [G]§ 63.1207(l)(2) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(k) § 63.1209(k)(1)(i) § 63.1209(k)(2)(i) § 63.1209(k)(2)(ii) [G]§ 63.1209(k)(3) [G]§ 63.1209(k)(4) § 63.1209(k)(5) [G]§ 63.1209(k)(6) [G]§ 63.1209(k)(7) [G]§ 63.1209(k)(8) [G]§ 63.1209(k)(9) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)	discharge or cause to be emitted into the atmosphere combustion gases that contain CO emissions in excess of the limits provided by §63.1217(a)(5) for sources not equipped with a dry air pollution control system;	[G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) [G]§ 63.1207(b)(2) [G]§ 63.1207(b)(3) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) § 63.1209(k)(2)(i) [G]§ 63.1209(k)(3) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	[G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) § 63.1209(k)(2)(i) [G]§ 63.1209(k)(3) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	[G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xix) § 63.1207(f)(1)(xv) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xviii) [G]§ 63.1207(f)(1)(xx) [G]§ 63.1207(f)(1)(xxi) § 63.1207(f)(1)(xxii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(2) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(k)(2)(i) [G]§ 63.1209(k)(3) [G]§ 63.1209(k)(8) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)		[G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-2	Mercury	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(2)(ii) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1)	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain Hg, except as provided for in paragraph §63.1217 (a)(2)(iii), when you burn hazardous waste with an as-fired heating value 10,000 Btu/lb or greater, emissions in excess of 4.2 x 10 ⁻⁵ lbs Hg attributable to the hazardous waste per million Btu heat input from the hazardous waste on an (not-to-exceed) annual averaging period.	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) [G]§ 63.1206(c)(6)(vii) [G]§ 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) [G]§ 63.1207(f)(1)(x) § 63.1207(f)(1)(xii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1207(m)(3) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) [G]§ 63.1209(l)(1)(v) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)		§ 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) [G]§ 63.1207(f)(1)(x) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1208(b)(2) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(a)(5) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)	[G]§ 63.1211(d)	§ 63.1207(f)(1)(xvi) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxvi) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1207(m)(5) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) § 63.1209(g)(1)(iv)(B) [G]§ 63.1209(l)(1)(v) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E02B030	EU	63EEE-2	Total Chlorine	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(6)(ii) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1207(m)(3) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(n)(4) § 63.1209(o) [G]§ 63.1209(o)(1)(ii)(A) [G]§ 63.1209(o)(2) [G]§ 63.1209(o)(3) § 63.1209(o)(4) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)	For existing liquid fuel boilers, you must not discharge or cause to be emitted into the atmosphere combustion gases that contain, except for an area source as defined under §63.2, when you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 5.08 x 10 ⁻² lbs combined emissions of hydrogen chloride and chlorine gas attributable to the hazardous waste per million Btu heat input from the hazardous waste.	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xi) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xvii) § 63.1207(g) § 63.1207(g)(1)(ii) § 63.1207(g)(2)(iii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) [G]§ 63.1207(m)(1) [G]§ 63.1207(m)(2) [G]§ 63.1208(b)(5)(i) § 63.1208(b)(5)(ii) [G]§ 63.1208(b)(5)(ii)(B) § 63.1208(b)(7) § 63.1208(b)(8)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) [G]§ 63.1207(f)(1)(ix) § 63.1207(m)(1) [G]§ 63.1207(m)(2) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xi) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xvi) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxv) § 63.1207(f)(1)(xxvi) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(iii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.1209(a)(5) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) § 63.1209(c)(5) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)		[G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1207(m)(5) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-2	Principal Organic Hazardous Constituent	40 CFR Part 63, Subpart EEE	§ 63.1217(c)(1) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k)	For liquid fuel boilers, except as provided in §63.1217(c)(2), you must achieve a DRE of 99.99% for each POHC designated under paragraph §63.1217(c)(3). You must calculate DRE for each POHC using the equation in §63.1217(c)(2).	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) § 63.1207(f)(1)(ii)(D) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5) [G]§ 63.1206(b)(7)(i) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(iii)(A) § 63.1207(f)(1)(iii)(B) § 63.1207(f)(1)(iii)(C) § 63.1207(f)(1)(iii)(D) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1207(l)(1) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) [G]§ 63.1209(j) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(c)(3)(i) § 63.1217(c)(3)(ii)		§ 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(b)(1) [G]§ 63.1209(b)(2) § 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) [G]§ 63.1209(j) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)	[G]§ 63.1211(d)	§ 63.1207(f)(1)(xii) § 63.1207(f)(1)(xix) § 63.1207(f)(1)(xvii) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a) [G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02B030	EU	63EEE-2	Total Hydrocarbo	40 CFR Part 63, Subpart EEE	§ 63.1217(a)(5)(i) [G]§ 63.1206(b)(5)	For existing liquid fuel boilers, you must not	[G]§ 63.1206(b)(12) [G]§ 63.1206(b)(5)	§ 63.1206(b)(11) [G]§ 63.1206(b)(12)	§ 63.1206(b)(11) [G]§ 63.1206(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			ns/CO		[G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(i) § 63.1206(c)(6)(ii) [G]§ 63.1206(c)(6)(iv) [G]§ 63.1206(c)(6)(v) [G]§ 63.1206(c)(6)(vi) [G]§ 63.1206(c)(7) § 63.1207(g)(1)(iii)(A) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1209(c)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(d) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1211(c)(1) § 63.1211(c)(2) § 63.1211(c)(4) § 63.1217(d)	discharge or cause to be emitted into the atmosphere combustion gases that contain CO in excess of 100 ppmv, over an hourly rolling average (monitored continuously with a CEMs), dry basis and corrected to 7 % O ₂ . If complying with this CO standard rather than the hydrocarbon standard under §63.1217(a)(5)(ii), hydrocarbons do not exceed 10 ppmv , and must be reported as specified.	[G]§ 63.1206(b)(6) [G]§ 63.1206(c)(3) § 63.1207(a) § 63.1207(b)(1) § 63.1207(c)(1) [G]§ 63.1207(c)(2) [G]§ 63.1207(d) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xxvii) § 63.1207(g) § 63.1207(g)(1)(ii) § 63.1207(g)(2)(i) § 63.1207(g)(2)(v) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(l)(1) § 63.1208(b)(7) § 63.1208(b)(8) § 63.1209(a)(1)(i) § 63.1209(a)(2) [G]§ 63.1209(a)(3) [G]§ 63.1209(a)(6) § 63.1209(a)(7) § 63.1209(b)(1) [G]§ 63.1209(b)(2)	[G]§ 63.1206(b)(5) [G]§ 63.1206(c)(1) [G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1206(c)(5) § 63.1206(c)(6)(vii) [G]§ 63.1206(c)(7) § 63.1207(f)(1)(xii) § 63.1207(g)(1)(iii)(A) § 63.1209(b)(1) [G]§ 63.1209(c)(2) [G]§ 63.1209(c)(4) [G]§ 63.1209(q) § 63.1211(b) [G]§ 63.1211(c)(3) [G]§ 63.1211(d)	[G]§ 63.1206(c)(2) [G]§ 63.1206(c)(3) [G]§ 63.1206(c)(4) [G]§ 63.1207(e) [G]§ 63.1207(f)(1)(i) § 63.1207(f)(1)(ii) § 63.1207(f)(1)(ii)(A) § 63.1207(f)(1)(ii)(B) § 63.1207(f)(1)(ii)(C) [G]§ 63.1207(f)(1)(iii) § 63.1207(f)(1)(iv) § 63.1207(f)(1)(ix) § 63.1207(f)(1)(v) § 63.1207(f)(1)(vi) § 63.1207(f)(1)(vii) § 63.1207(f)(1)(viii) § 63.1207(f)(1)(xii) § 63.1207(f)(1)(xviii) § 63.1207(f)(1)(xxvii) § 63.1207(f)(2)(i) § 63.1207(f)(2)(ix) § 63.1207(f)(2)(v) § 63.1207(f)(2)(vi) § 63.1207(f)(2)(vii) § 63.1207(f)(2)(viii) § 63.1207(f)(2)(x) [G]§ 63.1207(h) [G]§ 63.1207(i) [G]§ 63.1207(j)(1) § 63.1207(j)(3) § 63.1207(j)(4) § 63.1207(j)(5) [G]§ 63.1207(k) [G]§ 63.1207(l)(1) § 63.1207(l)(3) § 63.1209(c)(3) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) [G]§ 63.1209(g)(1)(iii) [G]§ 63.1210(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.1209(b)(3) § 63.1209(b)(4) [G]§ 63.1209(b)(5) [G]§ 63.1209(c)(4) [G]§ 63.1209(d) [G]§ 63.1209(f) § 63.1209(g)(1)(i) § 63.1209(g)(1)(ii) § 63.1209(i) § 63.1209(p) [G]§ 63.1209(q) § 63.1209(r)		[G]§ 63.1210(b)(1) § 63.1210(b)(2) § 63.1210(b)(3)(i) § 63.1210(c)(1)(i) § 63.1210(c)(2) [G]§ 63.1210(c)(3) [G]§ 63.1210(c)(4) [G]§ 63.1210(d) § 63.1211(a) [G]§ 63.1211(c)(3) [G]§ 63.1211(d) § 63.1212(a)
E02BCTR1	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
E02BCTR2	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
E02BCTR4	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in § 115.769(a)(3).			
E02BCTR5	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
E02BCTR6	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
E02BCTR7	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
E02BCTR9	EU	115H2	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E17A020	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
F02B0001	EU	61J	Benzene	40 CFR Part 61, Subpart J	§ 61.110(c)(2)	Any equipment in benzene service located at a plant that is designed to produce or use less than 1,000 megagrams (1,102 tons) of benzene per year are exempt from §61.112.	None	§ 61.110(c)(1) § 61.246(i) § 61.246(i)(1)	None
F02B001-01	EU	61J	Benzene	40 CFR Part 61, Subpart J	§ 61.110(c)(2)	Any equipment in benzene service located at a plant that is designed to produce or use less than 1,000 megagrams (1,102 tons) of benzene per year are exempt from §61.112.	None	§ 61.110(c)(1) § 61.246(i) § 61.246(i)(1)	None
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a)	Standards: Pressure relief devices in liquid service.	[G]§ 63.169 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) [G]§ 63.182(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	§63.169(a)-(d)	[G]§ 63.180(d)	§ 63.181(c) [G]§ 63.181(d)	§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	Owners/operators of closed-vent systems and control devices used to comply with provisions of this subpart shall comply with the provisions of this section, except as provided in §63.162(b).	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a)	Standards: Open-ended valves or lines. §63.167(a)-	[G]§ 63.175 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) [G]§ 63.182(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	(e).	[G]§ 63.180(d)	§ 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F02B001-01	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i)	All pumps that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I)) § 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I) II) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I)	All compressors that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I II) II) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I I) II)	All agitators that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C)	Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.786(a)(1)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) § 115.786(a)(1) § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) [G]§ 115.786(b)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within the process unit or processes listed in §115.780(a) in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(a)	Components that contact a process fluid containing less than 5.0% highly-reactive volatile organic compounds by weight on an annual average basis are exempt	None	§ 115.786(e) § 115.786(g)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from the requirements of this division (relating to Fugitive Emissions), except for 115.786(e) and (g) of this title (relating to Record keeping Requirements).			
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii)	Process drains within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a)	Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(f) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	[G]§ 115.788(g)
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1)	Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	processing operation which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B)	Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I)	Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I II) II) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I I) II) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)	Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I)) § 115.782(c)(1)(C)(i)(I) I) § 115.782(c)(1)(C)(i)(I) II) §	Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)				
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.358(c)(1) [G]§ 115.358(h) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(2) § 115.782(b)(3) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Components within the process unit or processes listed in §115.780(a) is subject to the requirements of this division. If the owner of operator elects to use the alternative work practice in §115.358 of this title, a leak is defined as specified in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) § 115.781(b) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(h)(1) § 115.781(h)(2) § 115.781(h)(3) § 115.781(h)(4) § 115.781(h)(5) [G]§ 115.781(h)(6) § 115.782(b)(4) § 115.782(d)(1) § 115.788(h)(1) [G]§ 115.788(h)(2) § 115.788(h)(3)	§ 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(4) § 115.356(5) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) [G]§ 115.786(f) § 115.786(g)	[G]§ 115.358(g) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F17A001	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B)
F17A001	EU	61J	Benzene	40 CFR Part 61, Subpart J	§ 61.110(c)(2)	Any equipment in benzene service located at a plant	None	§ 61.110(c)(1) § 61.246(i)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						that is designed to produce or use less than 1,000 megagrams (1,102 tons) of benzene per year are exempt from §61.112.		§ 61.246(i)(1)	
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				[G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g)	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171 [G]§ 63.175			[G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	§ 63.182(c)(4) [G]§ 63.182(d)
F17A001	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP UDTK1	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
LLENG1	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
LLENG1	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10),	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
LLENG1	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
LLENG1	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.			
LLENG1	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
LLENG2	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
LLENG2	EU	R7201	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
LLENG2	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
LLENG2	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
LLENG2	EU	63ZZZ-	112(B)	40 CFR Part 63,	§ 63.6590(c)	Stationary RICE subject to	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		01	HAPS	Subpart ZZZZ		Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
T03AD2054 T	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T03AD2427	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T03AD2550	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T03AIPDAN	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						psia is exempt from the requirements of this division.			
T03AIPDAS	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.113 § 115.910	Alternate means of compliance with the applicable control requirements or exemption criteria in this division may be approved per 30 TAC §115.910, if emission reductions are substantially equal.	None	None	None
T03AY2048 T	EU	R5137	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None
T03AY2050 T	EU	R5137	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None
W03A005	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
W03A005A	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary	85
Periodic Monitoring Summary	86

CAM Summary

Unit/Group/Process Information	
ID No.: E02B030	
Control Device ID No.: E02B030	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: 115VGC
Pollutant: VOC	Main Standard: § 115.121(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if the combustion temperature is less than 1194 degrees Fahrenheit.	
CAM Text: Each monitoring device shall be calibrated and maintained at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated and maintained properly.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 3RDSTENG1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 3RDSTENG2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 5PHENG1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 5PHENG2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 6PHENG1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 6PHENG2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: E02B030	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions.</p> <p>If the result of the Test Method 9 is an opacity above the corresponding opacity limit, the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: LLENG1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: LLENG2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if any visible emissions are observed.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Permit Shield

Permit Shield 96

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
E02B030	N/A	30 TAC Chapter 112, Sulfur Compounds	Fuel being used does not meet the definition of liquid fuel.
E02B030	N/A	40 CFR Part 60, Subpart Dc	Maximum design heat input capacity > 29 MW (100 MMBtu/hr)
E02B030	N/A	40 CFR Part 63, Subpart F	Vent gas stream is exempt because the gas stream is routed to fuel gas system, as defined by 63.101.
E02BCTR1	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR2	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR4	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR5	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR6	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR7	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E02BCTR9	N/A	40 CFR Part 63, Subpart Q	Cooling towers are not operated with chromium-based water treatment chemicals
E03AT5BST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessels stores something other than volatile organic compound.
E03AT5BST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
E03CIST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
E03CIST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
E03NAST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
E03NAST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
E03OSST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
E03OSST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
F02B0001	N/A	40 CFR Part 60, Subpart VV	Unit does not meet the definition of an affected facility pursuant to 60.480(a)(2) and 60.481
F02B0001	N/A	40 CFR Part 61, Subpart V	The facility is not intended to operate in VHAP service
F02B0001	N/A	40 CFR Part 63, Subpart H	Process unit is not a SOCM1 CMPI, therefore not applicable to Subpart H
F02B001-01	N/A	40 CFR Part 60, Subpart VV	NSPS VV superseded by MACT H
F02B001-01	N/A	40 CFR Part 61, Subpart V	The facility is not intended to operate in VHAP service
F17A001	N/A	40 CFR Part 60, Subpart VV	NSPS VV superseded by MACT H
F17A001	N/A	40 CFR Part 61, Subpart V	There are no sources, as listed in 61.240(a), intended to operate in VHAP service.
GRP UDTK1	T17ARSRH2O, T17ASH2O	40 CFR Part 60, Subpart K	The process vessel does not store petroleum liquid

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP UDTK1	T17ARSRH2O, T17ASH2O	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
GRP UDTK1	T17ARSRH2O, T17ASH2O	40 CFR Part 60, Subpart Kb	Pre 07/23/1984
T03AD2054T	N/A	40 CFR Part 60, Subpart Kb	Capacity is less than 19,800 gallons
T03AD2427	N/A	40 CFR Part 60, Subpart Kb	Capacity < 19,800 gallons
T03AD2550	N/A	40 CFR Part 60, Subpart Kb	Capacity < 19,800 gallons
T03AT1BDST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT1BDST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT1CIST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT1CIST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT1DST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT1DST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT5CIST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT5CIST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT5DST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT5DST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT5YMC1	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T03AT5YMC1	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT6BDST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT6BDST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT6CIST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT6CIST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
T03AT6DST	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel stores something other than volatile organic compound.
T03AT6DST	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL.
W03A005	N/A	40 CFR Part 60, Subpart Kb	Total vapor pressure of material stored in < 0.5 psia
W03A005A	N/A	40 CFR Part 60, Subpart Kb	Total vapor pressure of material stored is < 0.5 psia
W03ARECGW1	N/A	30 TAC Chapter 115, Water Separation	Any VOC water separator which is designed solely to capture storm water, spills, or exterior surface cleanup waters (or remediation activities) is exempt from this undesignated head
W03ARECGW2	N/A	30 TAC Chapter 115, Water Separation	Any VOC water separator which is designed solely to capture storm water, spills, or exterior surface cleanup waters (or remediation activities) is exempt from this undesignated head

New Source Review Authorization References

New Source Review Authorization References	101
New Source Review Authorization References by Emission Unit	102

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 2958A	Issuance Date: 11/08/2013
Authorization No.: 48988	Issuance Date: 02/17/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 03/14/1997
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 03/14/1997
Number: 106.532	Version No./Date: 09/04/2000
Number: 106.533	Version No./Date: 07/04/2004
Number: 8	Version No./Date: 10/04/1995
Number: 51	Version No./Date: 09/12/1989
Number: 51	Version No./Date: 04/05/1995
Number: 51	Version No./Date: 10/04/1995
Number: 51	Version No./Date: 06/07/1996
Number: 61	Version No./Date: 09/12/1989
Municipal Solid Waste and Industrial Hazardous Waste Permits With an Air Addendum	
Permit No.: HW-50242-001	

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
3RDSTENG1	FIRE WATER PUMP P-0981-1	106.511/09/04/2000
3RDSTENG2	FIRE WATER PUMP P-0981-2	106.511/09/04/2000
5PHENG1	FIRE WATER PUMP P-0985-1	106.511/09/04/2000
5PHENG2	FIRE WATER PUMP P-0985-2	106.511/09/04/2000
6PHENG1	FIRE WATER PUMP P-0986-1	106.511/09/04/2000
6PHENG2	FIRE WATER PUMP P-0986-2	106.511/09/04/2000
AS-2	OPDA AIR STRIPPER	106.533/07/04/2004
E02B030	BOILER NO.53	2958A
E02BCTR1	COOLING TOWER #1	8/10/04/1995
E02BCTR2	COOLING TOWER #2	8/10/04/1995
E02BCTR4	COOLING TOWER #4	8/10/04/1995
E02BCTR5	COOLING TOWER #5	8/10/04/1995
E02BCTR6	COOLING TOWER #6	8/10/04/1995
E02BCTR7	COOLING TOWER #7	8/10/04/1995
E02BCTR9	COOLING TOWER #9	8/10/04/1995
E03AT5BST	BIOCIDE SOLUTION TANK	106.532/09/04/2000
E03CIST	CORROSION INHIBITOR SOLUTION TANK	106.532/09/04/2000
E03NAST	NEUTRALIZING AMINE SOLUTION TANK	106.532/09/04/2000
E03OSST	OXYGEN SCAVENGER SOLUTION TANK	106.532/09/04/2000
E17A020	SOUR WATER LOADING	48988
F02B0001	EOB WW VENT FUGITIVES	48988, 106.261/11/01/2003, 106.262/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F02B001-01	ES RESIDUE FUGITIVES	2958A
F17A001	ES MFS FUGITIVES	48988
LLENG1	FIRE WATER PUMP P-0987-1	106.511/09/04/2000
LLENG2	FIRE WATER PUMP P-0987-2	106.511/09/04/2000
T03AD2054T	OPDA NAPL STORAGE TANK	106.533/07/04/2004
T03AD2427	LUBE OIL	106.472/09/04/2000
T03AD2550	LUBE OIL	106.472/09/04/2000
T03AIPDAN	WASTEWATER TANK	61/09/12/1989
T03AIPDAS	WASTEWATER TANK	61/09/12/1989
T03AT1BDST	BIODISPERSANT SOLUTION TANK	106.532/09/04/2000
T03AT1CIST	CORROSION INHIBITER SOLUTION TANK	106.532/09/04/2000
T03AT1DST	DISPERSANT SOLUTION TANK	106.532/09/04/2000
T03AT5CIST	CORROSION INHIBITER SOLUTION TANK	106.532/09/04/2000
T03AT5DST	DISPERSANT SOLUTION TANK	106.532/09/04/2000
T03AT5YMC1	YELLOW METAL CORROSION INHIBITER TANK	106.532/09/04/2000
T03AT6BDST	BIODISPERSANT SOLUTION TANK	106.532/09/04/2000
T03AT6CIST	CORROSION INHIBITER SOLUTION TANK	106.532/09/04/2000
T03AT6DST	DISPERSANT SOLUTION TANK	106.532/09/04/2000
T03AY2048T	OPDA DNAPL SEPARATOR	106.533/07/04/2004
T03AY2050T	OPDA LNAPL SEPARATOR	106.533/07/04/2004
T17ARSRH2O	SOUR WATER STORAGE TANK	48988

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T17ASH2O	SOUR WATER TANK	48988
W03A005A	TRUCK UNLOADING TANK	48988
W03A005	WASTEWATER EQUALIZATION TANK	48988
W03ARECGW1	NORTH SEPARATIONS SYSTEM TANK	51/09/12/1989
W03ARECGW2	SOUTH SEPARATIONS SYSTEM TANK	51/09/12/1989

Appendix A

Acronym List 106

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound